

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: **B200 BOYSEN SEMI-GLOSS ENAMEL**

· Application of the substance / the preparation

Boysen Semi-gloss Enamel is an alkyd type paint that provides great durability while being noted as a fast drying paint. It is formulated to give a tough, durable, beautiful and high build film on wood and metal. Its superior hiding, combined with a semi-gloss finish, makes it easier to clean and resists wear and abrasion.

Principal Uses: For interior wood and metal surfaces

· Manufacturer/Supplier:

Pacific Paint (Boysen) Phils., Inc.
292 D. Tuazon St., Quezon City
1115 Philippines

· Further information obtainable from: Product safety department

· Information in case of emergency:

Telephone Nos.: +63 2 364 3505; +63 2 365 0561

Facsimile Nos.: +63 2 367 8878; +63 2 364 0472

Email Address : inquiry@boysen.com.ph

Website Address : www.boysen.com.ph

2 Hazards identification

· Hazard description:



T Toxic

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 45 May cause cancer.

R 46 May cause heritable genetic damage.

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

R 48 Danger of serious damage to health by prolonged exposure.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· GHS label elements



Danger

3.5/1B - May cause genetic defects.

3.6/1B - May cause cancer.

3.10/1 - May be fatal if swallowed and enters airways.



Danger

3.3/1 - Causes serious eye damage.

3.2/2 - Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 1)

**Warning**

2.6/3 - Flammable liquid and vapour.

**Warning**

3.8/3 - May cause drowsiness or dizziness.

4.1/3 - Harmful to aquatic life with long lasting effects.

Prevention:

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapours/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Avoid release to the environment.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Use personal protective equipment as required.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 IF ON SKIN: Wash with plenty of soap and water.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Immediately call a POISON CENTER or doctor/physician.
 Call a POISON CENTER or doctor/physician if you feel unwell.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 2)

Dangerous components:

CAS: 8008-20-6 EINECS: 232-366-4	Kerosine (petroleum) ✱ Xn, ✱ Xi, ✱ F, ✱ N; R 11-20-38-48-51/53-65-66-67 Danger: ✱ 2.6/2; ✱ 3.10/1 Warning: ✱ 3.1.1/4, 3.8/3; 3.2/3 ✱ 4.1.C/2	10-25%
CAS: 1317-65-3	Limestone ✱ Xi; R 37/38-41 Danger: ✱ 3.3/1, 3.2/2 Warning: ✱ 3.8/3	10-25%
CAS: 64742-81-0 EINECS: 265-184-9	Kerosine (petroleum), hydrodesulfurized ✱ Xn; R 65 Danger: ✱ 3.10/1	2.5-10%
CAS: 22464-99-9 EINECS: 245-018-1	Zirconium 2-ethylhexanoate 2-ethylhexanoic acid zirconium salt ✱ Xn, ✱ Xi, ✱ N; R 10-20/21-36/37/38-51/53-65 Danger: ✱ 3.1.D/3, 3.1.1/4, 3.2/2, 3.3/2A, 3.8/3; ✱ 3.10/1 Warning: ✱ 2.6/3 ✱ 4.1.C/2	≤ 2.5%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy Carc. Cat. 2, Muta. Cat. 2; ✱ T; R 45-46-65 Danger: ✱ 3.5/1B, 3.6/1B, 3.10/1 Warning: ✱ 2.6/3	≤ 2.5%

Additional information:

For the wording of the listed risk phrases refer to section 16.

CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	10-25%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide	10-25%

4 First aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.· **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

Suitable extinguishing agents:CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Person-related safety precautions:** Not required.**Measures for environmental protection:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 3)

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

· **Information about fire - and explosion protection:** Keep respiratory protective device available.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

8008-20-6 Kerosine (petroleum)

REL (USA)	100 mg/m ³
TLV (USA)	200 mg/m ³
as total hydrocarbon vapor; Skin; P	

64742-81-0 Kerosine (petroleum), hydrodesulfurized

REL (USA)	100 mg/m ³
TLV (USA)	200 mg/m ³
as total hydrocarbon vapor; Skin; P	

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 4)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100°C

· **Flash point:** Not applicable.

· **Ignition temperature:** 210°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: 0.7 Vol %

Upper: 5.0 Vol %

· **Vapour pressure at 20°C:** 23 hPa

· **Density:** 1.2093 - 1.2454 Kg/Li

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Viscosity:** 87 - 95 KU

· **Solvent content:**

Organic solvents: 24.9 %

Water: 17.9 %

VOC (EC) 303.2 g/L

· **Solids content:** 39.2 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

· **Dangerous decomposition products:** No dangerous decomposition products known.

(Contd. of page 5)

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
 Irritant
 Carcinogenic.
 The product can cause inheritable damage.

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **General notes:**
 Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
 Harmful to aquatic organisms

13 Disposal considerations

- **Product:**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1263
- **Packaging group:** III
- **Hazard label:** 3

(Contd. on page 7)

RP

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 6)

 · **Description of goods:** 1263 PAINT, special provision 640E

 · **Maritime transport IMDG:**

 · **IMDG Class:** 3
 · **UN Number:** 1263
 · **Label** 3
 · **Packaging group:** III
 · **EMS Number:** F-E,S-E
 · **Marine pollutant:** No
 · **Proper shipping name:** PAINT

 · **Air transport ICAO-TI and IATA-DGR:**

 · **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1263
 · **Label** 3
 · **Packaging group:** III
 · **Proper shipping name:** PAINT

 · **UN "Model Regulation":** UN1263, PAINT, 3, III

15 Regulatory information

 · **Philippines Inventory of Chemicals and Chemical Substances**

8008-20-6	Kerosine (petroleum)
1317-65-3	Limestone
13463-67-7	titanium dioxide
64742-81-0	Kerosine (petroleum), hydrodesulfurized
65996-63-6	Polysaccharide
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
68953-58-2	bis(hydrogenatedtallowalkyl)dimethylammoniumbentonite Ditallowdimethylammonium
22464-99-9	Zirconium 2-ethylhexanoate 2-ethylhexanoic acid zirconium salt
8030-76-0	Lecithin Phosphatidylcholine Vegetable Lecithin Lecithin soya bean Lecithin soybean Soybean Soyabean lecithin
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
136-52-7	cobalt bis(2-ethylhexanoate)
96-29-7	2-butanone oxime

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 7)

107-98-2	1-methoxy-2-propanol
64742-49-0	Naphtha (petroleum), hydrotreated light

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:


T Toxic

· Hazard-determining components of labelling:

Kerosine (petroleum)

Naphtha (petroleum), hydrodesulfurized heavy

· Risk phrases:

45 May cause cancer.

46 May cause heritable genetic damage.

38 Irritating to skin.

41 Risk of serious damage to eyes.

48 Danger of serious damage to health by prolonged exposure.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· Special labelling of certain preparations:

Contains cobalt bis(2-ethylhexanoate), 2-butanone oxime. May produce an allergic reaction.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

10 Flammable.

11 Highly flammable.

20 Harmful by inhalation.

20/21 Harmful by inhalation and in contact with skin.

36/37/38 Irritating to eyes, respiratory system and skin.

37/38 Irritating to respiratory system and skin.

38 Irritating to skin.

41 Risk of serious damage to eyes.

45 May cause cancer.

46 May cause heritable genetic damage.

48 Danger of serious damage to health by prolonged exposure.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2011

Revision: 12.01.2011

Trade name: B200 BOYSEN SEMI-GLOSS ENAMEL

(Contd. of page 8)

- 66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

Safety, Health and Environment Department

Gretchen A. Fontejon - g_fontejon@boysen.com.ph

Joanne C. Ysrael - joanneysrael@boysen.com.ph

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

· *** Data compared to the previous version altered. 12.01.2011**

RP