

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** **B50 BOYSEN LACQUER THINNER**
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation**
B50 Boysen Lacquer Thinner is a solvent used for lacquer types of paints.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Pacific Paint (Boysen) Phils., Inc.
292 D.Tuazon St., Quezon City
1115 Philippines
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:**
Telephone Nos.: +63 2 364 3505; +63 2 365 0561
Facsimile Nos.: +63 2 367 8878; +63 2 364 0472
Email Address : inquiry@boysen.com.ph
Website Address : www.boysen.com.ph

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 1B H350 May cause cancer.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45-46: May cause cancer. May cause heritable genetic damage.



Xn; Harmful

R48/20-63-65: Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Xi; Irritant

R36/38: Irritating to eyes and skin.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 1)

**F; Highly flammable****R11:** Highly flammable.**R67:** Vapours may cause drowsiness and dizziness.
Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements
Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:
**T Toxic****F Highly flammable**
Hazard-determining components of labelling:

toluene

Solvent naphtha (petroleum), light aliph.

Risk phrases:

45 May cause cancer.

46 May cause heritable genetic damage.

11 Highly flammable.

36/38 Irritating to eyes and skin.

48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.

63 Possible risk of harm to the unborn child.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

9 Keep container in a well-ventilated place.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 2)

· Dangerous components:		
CAS: 108-88-3 EINECS: 203-625-9	toluene Xn R48/20-63-65; Xi R38; F R11 R67 Repr. Cat. 3 Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one Xn R20; Xi R36/37; F R11 R66 Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 64742-89-8 EINECS: 265-192-2	Solvent naphtha (petroleum), light aliph. T Carc. Cat. 2, Muta. Cat. 2 R45-46; Xn R65 Carc. 1B, H350; Asp. Tox. 1, H304	10-25%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Xn R20/21/22; Xi R36/38 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 3)

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

108-88-3 toluene

PEL (USA)	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	75 mg/m ³ , 20 ppm BEI

67-64-1 acetone

PEL (USA)	2400 mg/m ³ , 1000 ppm
REL (USA)	590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m ³ , (500) NIC-200 ppm BEI
IOELV (EU)	1210 mg/m ³ , 500 ppm

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 4)

108-10-1 4-methylpentan-2-one	
PEL (USA)	410 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV (USA)	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI
IOELV (EU)	Short-term value: 208 mg/m ³ , 50 ppm Long-term value: 83 mg/m ³ , 20 ppm
111-76-2 2-butoxyethanol	
ACGIH (USA)	Short-term value: 20 ppm
PEL (USA)	240 mg/m ³ , 50 ppm Skin
REL (USA)	24 mg/m ³ , 5 ppm Skin
TLV (USA)	97 mg/m ³ , 20 ppm BEI
IOELV (EU)	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 98 mg/m ³ , 20 ppm Skin

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

55°C

· Flash point:

-19°C

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

240°C

· Decomposition temperature:

Not determined.

· Self-igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:

1.2 Vol %

Upper:

13.0 Vol %

· Vapour pressure at 20°C:

233 hPa

· Density:

0.80 - 0.90 Kg/L

· Relative density

Not determined.

· Vapour density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Segregation coefficient (n-octanol/water):

Not determined.

· Viscosity:

Dynamic:

Not determined.

Kinematic:

Not determined.

· Solvent content:

Organic solvents:

88.0 %

VOC (EC)

100.00 %

Solids content:

12.0 %

· Other information

No further relevant information available.

PH

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
 - **Sensitization:** No sensitizing effects known.
 - **Additional toxicological information:**
- The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
- Irritant
- Carcinogenic.
- The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
 - **Persistence and degradability** No further relevant information available.
 - **Behaviour in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
 - **Additional ecological information:**
 - **General notes:**
- Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
- Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
 - **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation**
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

PH

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2



Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1993
· ADR, IMDG, IATA	
· UN proper shipping name	1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE, ACETONE), special provision 640D
· ADR	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (TOLUENE, ACETONE)
· Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	II
· ADR, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Tunnel restriction code	D/E
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (TOLUENE, ACETONE), special provision 640D, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

(Contd. on page 9)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2011

Version number 2

Revision: 02.09.2011

Trade name: B50 BOYSEN LACQUER THINNER

(Contd. of page 8)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H350 May cause cancer.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.

R11 Highly flammable.
 R20 Harmful by inhalation.
 R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
 R36 Irritating to eyes.
 R36/37 Irritating to eyes and respiratory system.
 R36/38 Irritating to eyes and skin.
 R38 Irritating to skin.
 R45 May cause cancer.
 R46 May cause heritable genetic damage.
 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R63 Possible risk of harm to the unborn child.
 R65 Harmful: may cause lung damage if swallowed.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

Safety, Health and Environment Department
 Gretchen A. Fontejon - g_fontejon@boysen.com.ph

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered.**

02.09.2011

PH