

## 1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** **NS 965 FAST DRI ENAMEL MAPLE**

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Application of the substance / the preparation**

Nation Fast Dry Enamel is an alkyd type paint that provides durability and fast drying characteristics at an affordable price. It is intended to beautify and protect wood and metal surfaces.

PRINCIPAL USES: For exterior and interior wood and metal surfaces.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Pacific Paint (Boysen) Phils., Inc.  
292 D. Tuazon St., Quezon City  
1115 Philippines

· **Further information obtainable from:** Product safety department

· **Emergency telephone number:**

Telephone Nos.: +63 2 364 3505; +63 2 365 0561

Facsimile Nos.: +63 2 367 8878; +63 2 364 0472

Email Address : inquiry@boysen.com.ph

Website Address : www.boysen.com.ph

## 2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45: May cause cancer.



Xn; Harmful

R65: Harmful; may cause lung damage if swallowed.

R10: Flammable.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 1)

**· Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**· Label elements**
**· Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

**· Code letter and hazard designation of product:**


T Toxic

**· Hazard-determining components of labelling:**

Kerosine (petroleum), hydrodesulfurized

Kerosine (petroleum)

Naphtha (petroleum), hydrodesulfurized heavy

Naphtha (petroleum), hydrotreated light

**· Risk phrases:**

45 May cause cancer.

10 Flammable.

65 Harmful: may cause lung damage if swallowed.

**· Safety phrases:**

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

13 Keep away from food, drink and animal feedingstuffs.

15 Keep away from heat.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**· Other hazards**
**· Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures** Product is a mixture

· **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 64742-81-0	Kerosine (petroleum), hydrodesulfurized	10-25%
EINECS: 265-184-9	Xn R65	
	Asp. Tox. 1, H304	

(Contd. on page 3)

PH

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 2)

CAS: 8008-20-6 EINECS: 232-366-4	Kerosine (petroleum) Xn R20-48-65; Xi R38; F R11; N R51/53 R66-67 Asp. Tox. 1, H304	10-25%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy T Carc. Cat. 2, Muta. Cat. 2 R45-46; Xn R65 Carc. 1B, H350; Asp. Tox. 1, H304	≤ 2.5%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light T Carc. Cat. 2, Muta. Cat. 2 R45-46; Xn R65 Carc. 1B, H350; Asp. Tox. 1, H304	≤ 2.5%
CAS: 13586-82-8 EINECS: 237-015-9	Cobalt Carboxylate Xn R22; Xi R36/37/38; Xi R43; N R51/53 R10 Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≤ 2.5%
CAS: 136-52-7 EINECS: 205-250-6	cobalt bis(2-ethylhexanoate) Xn R68; Xi R36/37/38; Xi R43 R10 Flam. Liq. 3, H226; STOT SE 2, H371; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≤ 2.5%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime Xn R21; Xi R41; Xi R43 Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317	≤ 2.5%

**Additional information:**

For the wording of the listed risk phrases refer to section 16.

CAS: 20344-49-4 EINECS: 243-746-4	iron hydroxide oxide	2.5-10%
CAS: 65996-63-6	Polysaccharide	≤ 2.5%
CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	25-50%

### 4 First aid measures

· **Description of first aid measures**· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Firefighting measures

· **Extinguishing media**· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.· **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 4)

PH

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 4)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

<b>64742-81-0 Kerosine (petroleum), hydrodesulfurized</b>	
REL (USA)	100 mg/m <sup>3</sup>
TLV (USA)	200 mg/m <sup>3</sup>
as total hydrocarbon vapor; Skin; P	
<b>8008-20-6 Kerosine (petroleum)</b>	
REL (USA)	100 mg/m <sup>3</sup>
TLV (USA)	200 mg/m <sup>3</sup>
as total hydrocarbon vapor; Skin; P	

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

PH

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 5)

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

· pH-value: Not determined.

#### · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100°C

· Flash point: 43°C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 210°C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### · Explosion limits:

Lower:	0.7 Vol %
Upper:	5.0 Vol %

· Vapour pressure at 20°C: 23 hPa

· Density: 0.92 - 1.02 Kg/Li

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Segregation coefficient (n-octanol/water): Not determined.

· Viscosity: 88 - 92 KU

· Dynamic: Not determined.

· Kinematic: Not determined.

#### · Solvent content:

Organic solvents:	33.3 %
Water:	31.1 %
VOC (EC)	482 g/Li

Solids content: 34.9 %

· Other information: No further relevant information available.

PH

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 6)

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >3000 mg/kg (rab)

- **Primary irritant effect:**
- **on the skin:** Cause mild irritation
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Carcinogenic.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

PH

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011



**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 7)

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· <b>UN-Number</b>	
· <b>ADR, IMDG, IATA</b>	UN1993
· <b>UN proper shipping name</b>	
· <b>ADR</b>	1993 FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrodesulfurized heavy, Cobalt Carboxylate), special provision 640E
· <b>IMDG, IATA</b>	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrodesulfurized heavy, Cobalt Carboxylate)
· <b>Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b>	3 (F1) Flammable liquids.
· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E,S-E
· <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 8)

**· Transport/Additional information:**
**· ADR**
**· Tunnel restriction code** D/E

**· UN "Model Regulation":** UN1993, FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrodesulfurized heavy, Cobalt Carboxylate), special provision 640E, 3, III

## 15 Regulatory information

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**
**· Philippines Inventory of Chemicals and Chemical Substances**

64742-81-0	Kerosine (petroleum), hydrodesulfurized
8008-20-6	Kerosine (petroleum)
20344-49-4	iron hydroxide oxide
65996-63-6	Polysaccharide
1309-37-1	diiron trioxide
13463-67-7	titanium dioxide
68953-58-2	bis(hydrogenatedtallowalkyl)dimethylammoniumbentonite Ditallowdimethylammonium
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
1317-61-9	triiron tetraoxide
64742-49-0	Naphtha (petroleum), hydrotreated light
13586-82-8	Cobalt Carboxylate
136-52-7	cobalt bis(2-ethylhexanoate)
96-29-7	2-butanone oxime
113163-32-9	Unsaturated Polar esters
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H350 May cause cancer.  
 H351 Suspected of causing cancer.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Version number 2

Revision: 02.12.2011

**Trade name: NS 965 FAST DRI ENAMEL MAPLE**

(Contd. of page 9)

H371 May cause damage to organs.  
H411 Toxic to aquatic life with long lasting effects.  
.....  
R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R21 Harmful in contact with skin.  
R22 Harmful if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R38 Irritating to skin.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitisation by skin contact.  
R45 May cause cancer.  
R46 May cause heritable genetic damage.  
R48 Danger of serious damage to health by prolonged exposure.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.  
R68 Possible risk of irreversible effects.

· **Department issuing MSDS:**

Safety, Health and Environment Department  
Gretchen A. Fontejon - g\_fontejon@boysen.com.ph

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent

· **\* Data compared to the previous version altered.**

02.12.2011

PH