

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** **B5815 BOYSEN ELASTIKOTE TOPCOAT**

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Application of the substance / the preparation**

Boysen Elasti-Kote is a 100% acrylic water based elastomeric wall paint that is especially formulated to bridge micro/ hairline cracks and crevices thus providing good waterproofing and protection from rain, carbon dioxide or other acidic gases (acid rain).

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Pacific Paint (Boysen) Phils., Inc.
292 D. Tuazon St., Quezon City
1115 Philippines

· **Further information obtainable from:** Product safety department

· **Emergency telephone number:**

Telephone Nos.: +63 2 364 3505; +63 2 365 0561

Facsimile Nos.: +63 2 367 8878; +63 2 364 0472

Email Address : inquiry@boysen.com.ph

Website Address : www.boysen.com.ph

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Sensitising

R43: May cause sensitisation by skin contact.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant

(Contd. on page 2)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2011

Version number 2

Revision: 12.01.2011

Trade name: B5815 BOYSEN ELASTIKOTE TOPCOAT

(Contd. of page 1)

Hazard-determining components of labelling:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hiso-thiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)

Risk phrases:

43 May cause sensitisation by skin contact.

Safety phrases:

- 2 Keep out of the reach of children.
 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
 24 Avoid contact with skin.
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
 37 Wear suitable gloves.
 46 If swallowed, seek medical advice immediately and show this container or label.

Other hazards
Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 471-34-1 EINECS: 207-439-9	calcium carbonate substance with a Community workplace exposure limit	10-25%
CAS: 111-46-6 EINECS: 203-872-2	2,2'-oxybisethanol Xn R22 Acute Tox. 4, H302	≤ 2.5%
CAS: 9004-62-0 EINECS: 217-576-6	Hydroxyethyl starch T R23/24/25; Xi R36/37/38 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≤ 2.5%
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hiso-thiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) T R23/24/25; C R34; Xi R43; N R50/53 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≤ 2.5%

Additional information:

For the wording of the listed risk phrases refer to section 16.

CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	25-50%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide	10-25%

4 First aid measures

Description of first aid measures
After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2011

Version number 2

Revision: 12.01.2011

Trade name: B5815 BOYSEN ELASTIKOTE TOPCOAT

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.*
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2011

Version number 2

Revision: 12.01.2011

Trade name: B5815 BOYSEN ELASTIKOTE TOPCOAT

(Contd. of page 3)

· Control parameters
· Ingredients with limit values that require monitoring at the workplace:

471-34-1 calcium carbonate	
PEL (USA)	15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
111-46-6 2,2'-oxybisethanol	
WEEL (USA)	10 mg/m ³

· Additional information: The lists valid during the making were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:
Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition
Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100°C

· Flash point: Not applicable.

(Contd. on page 5)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2011

Version number 2

Revision: 12.01.2011

Trade name: B5815 BOYSEN ELASTIKOTE TOPCOAT

(Contd. of page 4)

· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Vapour pressure at 20°C:	23 hPa
· Density:	1.21 Kg/Li
· Solubility in / Miscibility with water:	Fully miscible.
· Viscosity:	90 - 95 KU
· Solvent content:	
Organic solvents:	0.1 %
Water:	35.6 %
VOC (EC)	1.1 g/L
Solids content:	49.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Cause mild irritation
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2011

Version number 2

Revision: 12.01.2011

Trade name: B5815 BOYSEN ELASTIKOTE TOPCOAT

(Contd. of page 5)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

*

14 Transport information

- | | |
|---|-----------------|
| · UN-Number | |
| · ADR, IMDG, IATA | Void |
| · UN proper shipping name | |
| · ADR, IMDG, IATA | Void |
| · Transport hazard class(es) | |
| · ADR, IMDG, IATA | |
| · Class | Void |
| · Packing group | |
| · ADR, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | - |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Philippines Inventory of Chemicals and Chemical Substances**

471-34-1	calcium carbonate
13463-67-7	titanium dioxide
111-46-6	2,2'-oxybisethanol
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
9004-62-0	Hydroxyethyl starch
9036-19-5	Polyethylene glycol octylphenyl ether
330-54-1	diuron(ISO)
50-00-0	formaldehyde
10605-21-7	carbendazim (ISO)

(Contd. on page 7)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2011

Version number 2

Revision: 12.01.2011

Trade name: B5815 BOYSEN ELASTIKOTE TOPCOAT

(Contd. of page 6)

26530-20-1	2-octyl-2H-isothiazol-3-one
1336-21-6	ammonia
25322-68-3	Polyethylene glycol
7631-99-4	sodium nitrate, containing in the dry state more than 16,3 per cent by weight of nitrogen
10377-60-3	Magnesium nitrate 6-hydrate Magnesium (II), hexahydrate Nitric acid, magnesium salt, hexahydrate

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

R22 Harmful if swallowed.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R36/37/38 Irritating to eyes, respiratory system and skin.
R43 May cause sensitisation by skin contact.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Department issuing MSDS:**

Safety, Health and Environment Department
Gretchen A. Fontejon - g_fontejon@boysen.com.ph

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
VOC: Volatile Organic Compounds (USA, EU)

· *** Data compared to the previous version altered.**

12.01.2011

PH