BOYSEN
The No.1 PAINT

MATERIAL SAFETY DATA SHEET

PRODUCT
B2707

1.	CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME — BOYSEN MAHOGANY OIL WOOD STAIN

APPLICATION — OIL WOOD STAIN

Date Issued — 07-21-05

COMPANY IDENTIFICATION

Pacific Paints (Boysen) Philippines, Inc.
TEL: (632) 364-3505
(632) 365-0561 to 64
FAX: (632) 361-7164

2.	COMPOSITION/INFORMATION ON INGREDIENTS

The following chemical substance(s) are hazardous:

MATERIAL	CAS number	% (w/w)
Kerosene	64742-81-0	50.11

3.	HAZARDS IDENTIFICATION

HUMAN HEALTH HAZARDS-ACUTE
EYE CONTACT
Can cause irritation.

SKIN CONTACT
Can cause irritation.

INGESTION
Moderately toxic. May cause nausea and vomiting

INHALATION
Vapor or spray mist may cause irritation to the respiratory tract.

HUMAN HEALTH HAZARDS-CHRONIC
No harmful effects.

4. FIRST AID MEASURES

EYE CONTACT
Flush eyes immediately with water for at least 15 minutes. Get medical attention.

SKIN CONTACT
Wash thoroughly with soap and water.

INGESTION
Rinse mouth and drink lots of water. Get medical attention.

INHALATION
Move to fresh air.

5. FIRE FIGHTING MEASURES

FLASH POINT
≥38°C (based on solvent)

EXTINGUISHING MEDIA
Use carbon dioxide, dry chemical, or alcohol foam.

SPECIFICS HAZARDS
Gases of varying toxicity, such as CO and CO_2, may be produced because of incomplete combustion and thermolysis. These gases may be highly dangerous when inhaled.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTING
In case of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS
Wear protective equipment. Restrict access to unprotected persons.

METHODS FOR CLEANING UP
Soak up with inert absorbent (sawdust, sand). Dispose of contaminated material according to section 13.

7. HANDLING AND STORAGE

HANDLING
Do not take internally. Avoid contact with eyes or skin. Ensure adequate ventilation in the workplace. Keep away from heat and open flame. Do not expose to acids.

STORAGE CONDITIONS
Keep containers tightly closed. Store in a cool, dry, well-ventilated area suitable for flammable liquids. Protect from heat and direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES
General ventilation is recommended. Use of fume hood and/or local exhaust is preferred.

PERSONAL PROTECTION
RESPIRATORY PROTECTION
Not required for well-ventilated areas. In cases where inhalation is probable, use an appropriate respirator.

HAND PROTECTION
Butyl rubber, neoprene, or nitrile gloves.

SKIN PROTECTION
Wear standard protective clothing.

EYE PROTECTION
Wear safety goggles.

HYGIENE RECOMMENDATIONS
Maintain good personal hygiene to avoid exposure. Keep a safety shower available. If clothing is contaminated, wash immediately with water. Do not eat, drink, or smoke when handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	liquid
APPEARANCE	brown pigmented mixture
ODOR	characteristic odor
DENSITY	0.86 Kg/L @ 29°C
SOLUBILITY IN WATER	insoluble
VOC content	0.39 Kg/L

10. STABILITY AND REACTIVITY

STABILITY
Stable under normal conditions.

HAZARDOUS POLYMERIZATION
Hazardous polymerization will not occur.

CONDITIONS TO AVOID
High temperatures.

MATERIALS TO AVOID
Strong acids, alkalies, oxidants.

11. TOXICOLOGICAL INFORMATION

No toxicological studies have been made on this product.

12. ECOLOGICAL INFORMATION

No studies have been made on this product.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Presidential Decree No. 984-1976 ("The Pollution Control Law"), DENR Department Administrative Order No. 29-92 ("The Implementing Rules or Regulations of RA6969") and Presidential Decree No.825.

14. TRANSPORT INFORMATION

LAND/AIR/MARINE TRANSPORT:

Proper Shipping Name	Oil Wood Stain
Technical Name	Oil Wood Stain

Transport in accordance with the following legislation, as applicable:
Presidential Decree No. 1185, 1977 ("Fire Code of the Philippines")
Presidential Decree No. 856, 1975 ("Code of Sanitation")
Republic Act No 6969, 1990 ("Toxic Substances and Nuclear Wastes Control Act")

15. REGULATORY INFORMATION

Classification: FLAMMABLE

16. OTHER INFORMATION

COMPANY INFORMATION:
Pacific Paints (Boysen) Philippines, Inc.
292 D. Tuazon Street
1115 Quezon City
Philippines

EMERGENCY TELEPHONE NUMBER:
(632) 364-3505 loc 224

17.	DISCLAIMER

This information is to the best of our knowledge, accurate as of the date compiled. However, no representation is made to its accuracy, reliability, or completeness.