

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **B-1405 BOYSEN LATEX COLOR THALO GREEN**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Boysen Latex Colors are concentrated acrylic based tinting paints for Boysen Permacoat Latex Paints, Boysen Healthy Home and Boysen Wallguard Dirt Resisting Latex. They disperse easily and produce tints from pastel to medium shades with even finishes.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Pacific Paint (Boysen) Philippines, Inc.
292 D. Tuazon St., Quezon City
1115 Philippines

Further information obtainable from: Product safety department

1.4 Emergency telephone number:

Telephone Nos. : +63 2 364 3505; +63 2 365 0561
Facsimile Nos. : +63 2 367 8878; +63 2364 0472
Email Address : inquiry@boysen.com.ph
Website Address : www.boysen.com.ph

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Sensitising

R43: May cause sensitisation by skin contact.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2 Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

(Contd. of page 1)

Code letter and hazard designation of product:


Xi Irritant

Hazard-determining components of labelling:

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Risk phrases:

43 May cause sensitisation by skin contact.

Safety phrases:

2 Keep out of the reach of children.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

24 Avoid contact with skin.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

37 Wear suitable gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

2.3 Other hazards
Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 471-34-1 EINECS: 207-439-9	calcium carbonate substance with a Community workplace exposure limit	10-25%
CAS: 111-46-6 EINECS: 203-872-2	2,2'-oxybisethanol Xn R22 Acute Tox. 4, H302	½ 2.5%
CAS: 1336-21-6 EINECS: 215-647-6	ammonia C R34; N R50 Skin Corr. 1B, H314; Aquatic Acute 1, H400	½ 2.5%
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) T R23/24/25; C R34; Xi R43; N R50/53 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	½ 2.5%

Additional information:

For the wording of the listed risk phrases refer to section 16.

CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	25-50%
-------------------------------------	---	--------

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

(Contd. of page 2)

CAS: 14807-96-6 EINECS: 238-877-9	Talc ($Mg_3H_2(SiO_3)_4$)	 Carc. 2, H351	10-25%
CAS: 9016-45-9	Ethoxylated nonyl phenol		2.5-10%

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.

(Contd. on page 4)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

471-34-1 calcium carbonate

PEL (USA)	15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

111-46-6 2,2'-oxybisethanol

WEEL (USA)	10 mg/m ³
------------	----------------------

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

(Contd. of page 4)

· **Eye protection:** Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
 Colour: According to product specification
 Odour: Characteristic

· pH-value: 8.5-9.0

· Change in condition

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 100 °C

· Flash point: Not applicable.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Vapour pressure at 20 °C: 23 hPa

· Density: 1.23-1.25 Kg/Li

· Solubility in / Miscibility with water:

Fully miscible.

· Viscosity: 90-95 KU

· Solvent content:

Organic solvents: 1.8 %
 Water: 31.6 %
 VOC (EC) 11.7 g/L

Solids content: 66.1 %

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· Primary irritant effect:

· Skin corrosion/irritation Cause mild irritation

(Contd. on page 6)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

(Contd. of page 5)

- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|-----------------|
| · 14.1 UN-Number | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |

(Contd. on page 7)

PH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

(Contd. of page 6)

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not applicable.*

· **UN "Model Regulation":** -

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

· **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H301 *Toxic if swallowed.*

H302 *Harmful if swallowed.*

H311 *Toxic in contact with skin.*

H314 *Causes severe skin burns and eye damage.*

H317 *May cause an allergic skin reaction.*

H331 *Toxic if inhaled.*

H400 *Very toxic to aquatic life.*

H410 *Very toxic to aquatic life with long lasting effects.*

R22 *Harmful if swallowed.*

R23/24/25 *Toxic by inhalation, in contact with skin and if swallowed.*

R34 *Causes burns.*

R43 *May cause sensitisation by skin contact.*

R50 *Very toxic to aquatic organisms.*

R50/53 *Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

· **Department issuing MSDS:**

Safety, Health and Environment Department

Gretchen A. Fontejon - g_fontejon@boysen.com.ph

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.09.2015

Version number 8

Revision: 04.08.2010

Trade name: B-1405 BOYSEN LATEX COLOR THALO GREEN

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

**** Data compared to the previous version altered.***

04.08.2010

(Contd. of page 7)

PH